

# Warning Devices, Audible-Electronic WN-E

Measuring range -1 bar to 0 bar



Warning Devices, Audible-Electronic WN-E

## Design

- Electronic warning device with integrated electronic vacuum switch
- Electronics mounted in a robust, impact-resistant macrolon housing
- Electrical connection cable and hose for vacuum connection fed directly into the housing via cable gland

## Suitability for Industry Specific Applications

### Applications

- Warning device for system monitoring with warning if the vacuum drops or the electric power fails
- Monitoring of vacuum systems

## Product Highlights

- Electronic warning device for safe monitoring of the vacuum system
- Audible signal with 100 dB warns reliably even in loud environments
- Warning signal sounds thanks to voltage monitoring even in case of power failure
- Switching point customer-specific adjustable from -1 to 0 bar

## Designation Code Warning Devices, Audible-Electronic WN-E

WN-E	–	AKUST	–	-1...0 AC
1		2		3

### 1 – Abbreviated designation

Code	Version
WN-E	WN-E

### 2 – Principle of function

Code	Type
AKUST	Acoustic-electronic

### 3 – Voltage

Code	Voltage in V
-1...0 AC	Single-phase
-1...0 DC	Direct current

Warning device WN-E is delivered as a ready to connect product.